


MX Series Fixed Velocity Thickness Gauges



The **MX-1** and **MX-2** are fixed velocity gauges making them affordable precision tools that require no special training to operate.

The **MX-1** will hold a single velocity, making it the perfect choice where one material is being tested day after day. With the preset velocity in the gauge, you simply turn on the gauge and you are ready to work. The velocity is set in the **MX-1** with a simple software program that is supplied with the unit.

The **MX-2** is ideal for the person that tests a few different materials regularly. The MX-2 contains 8 velocities of common materials and 2 velocities that the user can set using a simple software program.

The **MX-1** and **MX-2** are packaged in all metal cases, sealed with gaskets to protect them from harsh working environments. These gauges can go where you go, to do the work you do, saving you time and money, making fast accurate measurements.

We offer MX-Series quality gauges that are reliable, innovative and competitively priced—all backed by the longest warranty in the business—5 full years.

THE MX SERIES THICKNESS GAUGES

The MX-Series rugged thickness gauge family has been designed and built to satisfy the roughest industry conditions. The variety of features offered in the **MX-Series** thickness gauges will allow the user to select a quality tool that will meet or exceed their specific application needs. Our 5 year limited warranty indicates how we feel about the reliability and durability of the new **MX Series**.

S P E C I F I C A T I O N S

Physical (all MX units)

Weight:

10 ounces (with batteries).

Size:

2.5 W x 4.5 H x 1.24 D inches
(63.5 W x 114.3 H x 31.5 D mm).

Operating Temperature:

-20P to 120PF (-30P to 50PC).

Case:

Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed).

Keypad (all MX units)

Sealed membrane that is resistant to both water and petroleum products.

Six tactile-feedback keys.

Transducer (all MX units)

Dual-element (transmit and receive).

1 to 10 MHz frequency range.

Locking quick disconnect LEMO connectors.

4 foot cable.

Custom transducers available for special applications.

Power Source (all MX units)

Two 1.5V alkaline or 1.2V NiCad AA cells.

Typically operates for 200 hours on alkaline and 130 hours on NiCad.

Display flashes when battery is low. Unit turns off automatically when battery is too low to operate reliably.

Display (all MX units)

Multi-function 4.5 digit liquid crystal display with 0.500 inch numerals, backlit for use in poor light conditions.

Backlight is selectable on/off/auto (illuminates only when taking a measurement).

Measurements displayed in inches, inches/microsecond, millimeters, and meters/second.

Bar graph indicates stability of reading.

Certification (all MX units)

Factory calibration traceable to national standards.

Warranty (all MX units)

5 year limited.

Measuring (all MX units)

Range:

Measures from 0.025 to 19.999 inches (0.63 to 500 millimeters).

Switch to select English or Metric units.

Resolution:

0.001 inch (0.01 millimeter)

Velocity Range:

0.0492 to .3937 in./ μ s.
(1250 to 10,000 meters/second)

Four readings per second for single point measurements or 16 per second in Scan Mode—captures the minimum thickness.

Single and two point calibration option included.



Distributed by:

Please feel free to call for more information

QUALITEST USA LC

3706 N. Ocean Blvd., #200
Ft. Lauderdale, FL 33308, USA
Toll-Free: 1.877.884.TEST (8378)
Fax : 954.697.8211
Website: www.WorldofTest.com
Email: info@qualitest-inc.com