

## PositestDFT® Coating Thickness Gage

### Ideal for...

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

### Two Models

- **PosiTest DFT Ferrous**  
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**  
measures both non-magnetic coatings on steel

AND non-conductive coatings on aluminum, brass, etc.  
Automatically recognizes the substrate and takes a measurement.



### Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mills/Microns switchable
- Basic instructions on the back of each gage

### Specifications

<b>Measurement Range</b>	0 – 40 mils	0 – 1000 µm
<b>Accuracy</b>	±(0.1 mils + 3%)	±(2µm + 3%)
<b>Size</b>	4 x 1.5 x 0.9 in.	100x38x23 mm
<b>Weight</b>	2.5 oz.	70 g



**Gage Comes Complete**  
with built-in probe, plastic shims,  
hard shell storage case, AAA battery,  
instructions and one (1) year warranty.

Conforms to: ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/  
B499/B659/D1186/D1400/E376/G12, BS3900-C5, SSPC-PA2 and  
others. Certificate of Calibration traceable to NIST available.